

P08

Highlights from two years of geoelectrical monitoring of permafrost at the Magnetköpfl/Kitzsteinhorn

Jochum Birgit¹, Ottowitz David¹, Pfeiler Stefan¹, Supper Robert¹, Keuschnig Markus², Hartmeyer Ingo², Kim Jung-Ho³

¹Geological Survey of Austria

²University of Salzburg and Alps

³Korean Institute of Geoscience and Mineral Resources (KIGAM)

Changes of climate parameters due to global warming generate increased permafrost warming and deglaciation in alpine regions. The area of interest is the Magnetköpfl, a peak below the Kitzsteinhorn (3203 m), where scientists observe increasing rock instability due to the probable degradation of permafrost as well as the decrease of glacier height followed by a lack of counter pressure at the flanks of the slope. Geoelectric measurements are an adequate method to measure permafrost, since the underground electric resistivity is highly dependent on temperature and the amount of unfrozen pore water. In October 2011 a geoelectrical monitoring profile with the GEOMON4D was installed on the north facing ridge of the Magnetköpfl. Measurements of soil temperature on the profile support the interpretation of geoelectric data.

The permafrost at Magnetköpfl starts at a depth of approximately 3m below surface and seasonal temperature variations below 0°C can be observed down to 8-10 m below surface. The two year period of data collection allows us to analyse time series of average apparent resistivities compared with the climatic seasons. It can be seen that different temperature periods have a direct correlation to average apparent resistivity. Inversion results of geoelectrical monitoring data are derived from an innovative 4D resistivity inversion approach (Kim et al, 2013). In three selected events (thawing and freezing in spring, thawing in summer, freezing in fall) difference images of the 4D inversion show the depth range of the temperature influence. Since the temperature sensors at the profile only reach 0.8m bgl., the geoelectrical monitoring data can deliver far more information than single point temperature measurements since the underground electric resistivity is highly dependent on temperature.

The geoelectrical monitoring is supported by the project "TEMPEL", funded by the Federal Ministry for Transport, Innovation & Technology (BMVIT) and the Austrian Science Fund (FWF): TRP 175-N21 and internal funds of the Geological Survey of Austria. The recording of the soil temperature is conducted in the framework of the MOREXPART project by the University of Salzburg and Alps.